

Energy Star Homes Evaluation

Location: New Orleans, LA

Energy Star Rating: 85.7



Energy Related Characteristics For Hot Climates Typical 3 Bedroom Frame House

Heating System
Gas Furnace, 80 AFUE

Cooling System
A/C, 10 SEER

Water Heating System
Gas Water Heater, 0.56 EF

Duct Leakage
10% (CFM25_{Total}=105)

Estimated Infiltration
7.0 ACH @ 50 pascal's

Areas (sq.ft.)
Condition floor - 1050
Windows - 126
Ceiling Area - 1050
Insulated Ex. Wall - 1010 (net)

Insulation
Ceiling: R-30
Walls: R-13+1" Rigid
Floor: Slab, Un-insulated
Ducts: R-6

Windows
Double Clear-Vinyl Frame
U-Value=0.49
SHGC=0.56

Energy Evaluation Results

Estimated Annual Energy Use: 50.7 MBtu
Estimated Annual Energy Cost: \$769

The Energy Star program awards the "Energy Star Home" designation to homes scoring 86 points or more on the Home Energy Rating Scale (HERS). A score of 86 indicates that a home is 30% more efficient than a standard reference home which scores an 80. Implementing one of the Energy Star packages below would bring this home's score up above 86. You may also request evaluation of other improvements or packages of improvements. Annual energy costs are calculated using an electric rate of \$0.08/kWh and a gas rate of \$0.50/Therm.

Energy Star Single Proposed Changes

1. Wall: R-13+2" Rigid Insulation
2. Windows: Double Pane/LowE/Argon Fill/Vinyl Frame#2,
U=0.32 SHGC=0.3
3. Heating Equipment: Furnace, 95 AFUE
4. Cooling Equipment: Increase to 12 SEER

HERS Score

1. 86.0
2. 86.7
3. 86.1
4. 87.1

Produced by:

Florida Solar Energy Center
1679 Clearlake Road, Cocoa, Florida 32922
Fax: (321)638-1439

Janet McIlvaine
Phone: (321) 638-1434
E-mail: janet@fsec.ucf.edu

Matthew Lombardi
Phone: (321)638-1421
E-mail: mlombardi@fsec.ucf.edu

General Guidance for ENERGY STAR Homes for Habitat for Humanity

Location: New Orleans, LA (Hot)

HDD = 1,490; CDH = 28,605

Building Component	Base Case House ¹ HERS Rating = 85.7	Proposed Changes	Potential Point Value ^{2,3} of proposed Change	Cost
Wall Insulation	R-13+1" Rigid Insulation	R-11 No Rigid Insulation	-0.4	
		R-11+1/2" Rigid Insulation	-0.2	
		R-13 No Rigid Insulation	-0.2	
		R-13+1/2" Rigid Insulation	-0.1	
		R-13+2" Rigid Insulation	0.3	
		R-15 No Rigid Insulation	-0.2	
		R-19 No Rigid Insulation	0.1	
Windows	Double Pane Clear-Vinyl Frame	Single Pane Clear-Vinyl Frame, U=0.9 SHGC=0.63	-0.8	
		Single Pane High Performance, U=0.9 SHGC=0.54	-0.6	
		Double Pane/LowE/Argon Fill/Vinyl Frame#2, U=0.32 SHGC=0.3	1	
Attic Insulation	R-30	Increase to R-38	0.1	
		Increase to R-50	0.2	
		R-30 + Radiant Barrier	0.2	
Heating Equipment	Gas Furnace, 80AFUE	Furnace, 95AFUE	0.4	
Cooling Equipment	A/C, 10 SEER	Increase to 12 SEER	1.4	
Water Heating Equipment	Gas Water Heater, 0.56EF	Gas Instantaneous, 0.65EF	1.7	
		Gas Tank, 0.56EF, R-5	0.5	
		Elec Tank, 0.9EF	0.1	
Duct Leakage	10% (CFM25 _{Total} = 105) ⁽⁴⁾	3% (CFM25 _{Total} = 31.5) ⁽⁴⁾	0.5	

¹ Typical 3 bedroom home described on the "Energy Star Homes Evaluation" for this location.

² Indicates change in HERS ENERGY STAR rating with each enhancement incorporated individually into the Habitat Home. A score of 86 qualifies a home for ENERGY STAR status and indicates 30% saving in combined heating, cooling, and water heating energy use compared to a standard Reference Home.

³ **IMPORTANT: Potential Point Values are not additive. Combinations must be evaluated by a Certified Rater to verify effective score.**

⁴ Duct leakage is shown as a % of conditioned floor area. For example, if CFM25=65, then leakage = 65/1050 = 6.2%.

Produced By:

Florida Solar Energy Center
1679 Clearlake Road
Cocoa, Florida 32922
Fax: (321) 638-1439

Janet McIlvaine
Phone: (321) 638-1434
Email: Janet@fsec.ucf.edu

Kevin McCluney
Phone: (321) 638-1000, ext 1222
Email: KMcCluney@fsec.ucf.edu

Matthew Lombardi
Phone: (321) 638-1421
Email: Mlombardi@fsec.ucf.edu